

Item No.	Description	Unit	Qty	Rate	Amount
	<u>SECTION No.2</u>				
	<u>BILL No. 2</u>				
	<u>CONCRETE, FORMWORK AND REINFORCEMENT</u>				
	<u>CONCRETE</u>				
	<u>UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES</u>				
2.1	<u>20MPa/20mm. concrete</u>				
2.1.1	Strip footings	m³	39		R -
2.1.2	Bases-wall	m³	10		R -
2.2	<u>TEST BLOCKS</u>				
2.2.1	Making and testing a set of three 150 x 150 x 150mm. concrete strength test cubes (Provisional)	no	8		R -
2.3	<u>FORMWORK</u>				
2.3.1	Rough formwork to sides Bases-wall	m²	46		R -
2.4	<u>PRECAST CONCRETE</u>				
2.4.1	370 X 75mm thick overall copings(Type 14) weathered on top to 65mm thick along one edge with drip grooves in bottom along both edges	m	200		R -
	<u>PAVING</u>				
	Approved brand of anti-termite soil posion and weedkiller is to be applied under paving by a Registered Company and guaranteed for ten years.				
	Paving shall be laid in accordance with SABS 1200MJ, SABS 1058 and the Concrete Masonry Association's specifications.				
	Paving shall be laid on 20mm (thickness after final or filling elsewhere).				
	Clean plaster sand shall be swept into joints between roadstones.				
2.5	<u>60mm Thick "Infraset Cottage Stone" standard TAN coloured clay pavers bedded on and including 20mm thick bed of river sand:</u>				
2.5.1	Paving to pavements, pathways, etc. to falls including any consequent cutting (circular cutting elsewhere).	m²	200		R -
<u>CONCRETE, FORMWORK AND REINFORCEMENT CARRIED TO SECTION SUMMARY</u>		R			-